



BRIEF INFORMATION

LED side marker light

- → For 12 and 24 Volt applications
- → Luminous surface for improved safety; modern night design
- → For horizontal flush-mounting

PRODUCT CHARACTERISTICS



Low energy consumption

HELLA signal lamps achieve the legally prescribed light distribution through a combination of efficient light-emitting diodes (LEDs) and precision optics – and use 80% less power than bulb-based lamps!

Night design

The design is emphasised by the large-scale illumination provided, especially on the sides of the vehicle. This follows the trend within the automotive industry of stylishly accentuating lighting elements, particularly for night designs.


Multivolt technology


Multivolt circuits keep the light output constant over a voltage range of 8 to 32 volts. This allows the same HELLA combination signal light to be used for both 12 and 24 volt applications. Multivolt also compensates for voltage fluctuations, which arise through the use of long cables and plug-type connections within the vehicle electric system. HELLA Multivolt circuits are also protected against reverse polarity and voltage peaks – even at low battery voltages.


TECHNICAL DETAILS

| TECHNICAL DATA | | | |
|------------------------------|--|--|--|
| Type approval | ECE | | |
| Rated voltage | 12 V and 24 V | | |
| Operating voltage | 8 – 32 V Multivolt | | |
| Functions | Side marker light without reflector | | |
| Number of LEDs | 1 | | |
| Power consumption | 0.5 W / 12 V 1.0 W / 24 V | | |
| Operating temperature | -40 °C - +50 °C | | |
| Protective category | IP 6K6, IP 6K7 | | |
| Contacting | Two-core coated cable, 500 mm, open cable end | | |
| Installation | With 2 screws Ø 4 mm | | |
| Polarity reversal protection | Yes | | |
| Specification | HELLA standard 67001, class 10 | | |
| Type approval | © 0004 ■ 03 2080 | | |
| Service life | 30,000 h* (* dependent upon the operating temperature) | | |
| Scope of supply | Two protective caps for screw heads; rubber seal | | |

Dimensional sketch







RANGE OVERVIEW

| Product image | Description | Part Number | PU |
|---------------|-------------------|-----------------|---------------|
| | Side marker light | 2PS 959 788-002 | Set, 2 pieces |
| | | 2PS 959 788-007 | 30 pieces |
| | Position light | 2PF 959 590-202 | Set, 2 pieces |
| | Clearance light | 2XA 959 790-401 | Set, 2 pieces |

Future offerings: Side marker light with transparent cover lens available upon request



Side marker light

2PS 959 788-102

Set, 2 pieces

2PS 959 788-107

30 pieces