



Hella KGaA Hueck & Co.
59552 Lippstadt

Technical Bulletin

Date: 2015-09-09

No.:

Page 1

Subject:

LCA 2.0 – Lane Change Assistant

Author: Wixforth

Org: E-ED-DAS-DR

Ref.:

Enclosures:

Short Description

The LCA is an advanced driver assistant system, to warn the driver of the subject vehicle against potential collisions with vehicles to the side or to the rear of the subject vehicle, and moving in the same direction as the subject vehicle during lane change manoeuvres. The system therefore detects vehicles to the rear and sides of the subject vehicle. The system will not take any automatic action to prevent possible collisions. Responsibility for the safe operation of the vehicle remains with the driver.

The LCA consists of two radar sensor units which are mounted behind the rear bumper in the left and right rear corners of a car so that the rear and the sides of the car can be observed.

Technical Data

| | |
|-----------------------------|---|
| Part Numbers | LCA 2.0 / LCA 2.0 A |
| Supply Voltage & Current | 9 V ... 16,5 V 0,36 A |
| EIRP | < +12,7 dBmW average < +20 dBmW peak |
| Transmit Antenna Gain | 15 dBi |
| Antenna Type | microstrip patch array |
| Modulation | FMCW |
| Frequency Band 1 | 24075 MHz ... 24175 MHz |
| Modulation Bandwidth | < 100 MHz |
| Frequency Band 2 | 24150 MHz ... 24250 MHz |
| Modulation Bandwidth | < 100 MHz |
| Frequency Band 3 | 24050 MHz ... 24250 MHz |
| Modulation Bandwidth | < 200 MHz |
| Operating Temperature Range | -40...70°C |
| Number of PCBs | 2 |
| Dimensions | 102 * 86 * 34 mm |
| Volume | < 300 cm ³ |
| Weight (OEM-value) | < 265 g |
| Housing material | Al diecasting |

signed by:

checked by: