



Hella KGaA Hueck & Co.
59552 Lippstadt

Technical Bulletin

Date: 2015-09-09

No.:

Page 1

Subject:

LCDAS - Lane Change Decision Aid System

Author: Wixforth/Schade

Org: E-ED-DAS-DR

Ref.:

Enclosures:

Short Description

The LCDAS is an advanced driver assistant system, to warn the driver of the subject vehicle against potential collisions with vehicles to the side and/or to the rear of the subject vehicle, and moving in the same direction as the subject vehicle during lane change manoeuvres. The system therefore detects vehicles to the rear and sides of the subject vehicle.

When the subject vehicle driver indicates the desire to make a lane change, the system will evaluate the situation and warn the driver if a lane change is not recommended. LCDAS are not meant to encourage aggressive driving. The absence of a warning will not guarantee that the driver can safely make a lane change manoeuvre. The system will not take any automatic action to prevent possible collisions. Responsibility for the safe operation of the vehicle remains with the driver.

Technical Data

Part Numbers	LCDAS 1.5
Supply Voltage & Current	9 V ... 15 V 0,5 A
EIRP	< +20 dBmW peak
Transmit Antenna Gain	16 dBi
Antenna Type	microstrip patch array
Modulation	FMCW
Frequency Band 1	24075 MHz ... 24175 MHz
Modulation Bandwidth	< 100 MHz
Frequency Band 2	24150 MHz ... 24250 MHz
Modulation Bandwidth	< 100 MHz
Operating Temperature Range	-40...+70°C
Number of PCBs	2
Dimensions	102 * 86 * 34 mm
Volume	< 300 cm ³
Weight (OEM-value)	< 265 g
Housing material	Al diecasting

signed by:

checked by: