Suzi Coil with 7P ISO 1724 / AS 2513 Plugs

Cable outlet: PG Gland. Outer Coil Diameter: 50mm.



8KA 227 440-101		
Housing	Silver coloured break-proof metal	
Maximum Working Length	4.6m	
Cable Outlet	PG Gland	
Wire Cross Section Area	6 x 1.5 mm ² + 1 x 2.5 mm ²	
Tail Ends	Tail 1: 220 mm, Tail 2: 220 mm	

Suzi Coil with 7P ISO 1724 / AS 2513 Plugs Long tail

Cable outlet: PG Gland.
Outer Coil Diameter: 50mm.



8KA 227 440-111 - Long Tail		
Housing	Silver coloured break-proof metal	
Maximum Working Length	5.6m	
Cable Outlet	PG Gland	
Wire Cross Section Area	6 x 1.5 mm ² + 1 x 2.5 mm ²	
Tail Ends	Tail 1: 300 mm, Tail 2: 1300 mm	

Suzi Coil with Heavy Duty 7P SAEJ 560 Plugs

These 7 pin spiral cable-plug assemblies are designed to provide a superior electrical connection between the Prime mover and trailer. The uni-molded connector bodies are extremely robust providing best in class performance and are completely unique to the market.

- High performance crimped contacts
- Integrated strain relief provides permanent kink protection
- Resistant to diesel fuel, engine coolant, engine oil, gear oil, water, salt, dirt, UV radiant and impact resistance.



8KA 905 392-041	
Housing	Uni-molded connector body seals out water and corrosive chemicals
Cable Outlet	Molded, bending protection
Wire Cross Section Area	4 x 3 mm ² + 2 x 5 mm ² + 1 x 8 mm ²
Max. Working Length	4m
Max. Extension Length	4.5m

Suzi Coil with 7P AS 2513 to SAE J560

Outer Coil Diameter: 50mm. Maximum working length 4.6m.



BKA 227 440-141 Housing ISO plug: Silver coloured break-proof metal SAE plug: Reinforced composite plastic Pins 7 Maximum Working Length 4.6m Wire Cross Section Area 6 x 1.5 mm² + 1 x 2.5 mm² Tail Ends Tail 1: 300 mm, Tail 2: 300 mm

BKA 227 440-151 - Long Tail Housing ISO plug: Silver coloured break-proof metal SAE plug: Reinforced composite plastic Pins 7 Maximum Working Length 5.6m Wire Cross Section Area 6 x 1.5 mm² + 1 x 2.5 mm² Tail Ends Tail 1: 300 mm, Tail 2: 1300 mm

Suzi Coil with 7P AS 2513 to SAE J560

Outer Coil Diameter: 50mm. Maximum working length 5.6m.



8JA 227 440-121	
Current	16A
Housing	Reinforced Plastic
Contact Surface	Nickel

7P Trailer Adaptor 13P to 7P

Mini Short Adaptor from vehicle 13P /12V to trailer 7P/12V.



8KA 227 440-131	
Housing	Break-proof silver coloured metal Housing plug with PVC cable
Cable Length	3m Maximum
Cable Outlet	PG Gland
Wire Cross Section Area	7 x 1.5 mm ²

Straight Cable with 7P ISO 1724 / AS 2513 Plugs

