

7P/12V ABS/EBS Socket with Screw Contacts

Made of reinforced composite with cover and rubber seals, and high strength cable gland of the cable outlet.



8JB 227 440-011

Operating voltage	12V DC
Pins	7
Housing	Reinforced Composite
For Cable	9 - 16mm
Contact Termination	Screw Contact
Standard	ISO7638-2

7P/12V ABS/EBS Plug with Screw Contacts

Made of reinforced composite with rubber seals. Mechanical strain relief.



8JA 227 440-031

Operating voltage	12V DC
Pins	7
Housing	Reinforced Composite
For Cable	9 - 16mm
Contact Termination	Screw Contact
Standard	ISO7638-2

Suzi Coil with 7P/12V ABS/EBS Plug

Max 4.5m cable length with plug at both ends and bending protection grommet. Outer cable dia: 50mm.



8KA 227 440-051

Operating voltage	12V DC
Pins	7
Max. Working Length	4m
Max. Extension Length	4.5m
Standard	ISO7638-2

8JB 227 440-021

Operating voltage	24V DC
Pins	7
Housing	Reinforced Composite
For Cable	9 - 16mm
Contact Termination	Screw Contact
Standard	ISO 7638-1

**7P/24V ABS/EBS Socket
with Screw Contacts**

Made of reinforced composite, with cover and rubber seals, and a high strength cable gland at the cable outlet. colour coded for easy installation.



8JA 227 440-041

Operating voltage	24V DC
Pins	7
Housing	Reinforced Composite
For Cable	9 - 16mm
Contact Termination	Screw Contact
Standard	ISO 7638-1

**7P/24V ABS/EBS Plug
with Screw Contacts**

Made of reinforced composite with rubber seals. Mechanical strain relief. colour coded for easy installation.



8KA 227 440-061

Operating voltage	24V DC
Pins	7
Max. Working Length	4m
Max. Extension Length	4.5m
Standard	ISO 7638-1


Suzi Coil with 7P/24V ABS/EBS Plug

Max 4.5m cable length with plug at both ends and bending protection grommet. Outer cable dia: 50mm.



Suzi Coil without Plug

Working length: 4.5 meters.
Temperature range: -40°C to 100°C.
Outer coil diameter: 50mm.
Suitable for ABS/EBS connections
with appropriate plugs



8JA 227 440-071

Wire Cross Section	5 x 1.5mm ²
Area	2 x 4 mm ²

Suzi Coil with 7P / Multivolt™
ABS/EBS Plug

Temperature range: -40°C to 100°C.
Outer Coil Diameter: 50mm.



8KA 227 440-081

Operating Voltage	Multivolt™*	
Pins	7	
Maximum Working Length	8KA 227 440-081	4.5m
Wire Cross Section Area	5 x 1.5 mm ² + 2 x 4.0 mm ²	
Tail Ends	8KA 227 440-081	Tail 1: 300 mm, Tail 2: 300 mm

*Caution: Operator must confirm voltage compatibility of prime mover and trailer.

Suzi Coil with 7P / Multivolt™
ABS/EBS Plug Long Tail

Temperature range: -40°C to 100°C.
Outer Coil Diameter: 50mm.



8KA 227 440-181 - Long tail

Operating Voltage	Multivolt™*	
Pins	7	
Maximum Working Length	8KA 227 440-181	5.2m
Wire Cross Section Area	5 x 1.5 mm ² + 2 x 4.0 mm ²	
Tail Ends	8KA 227 440-181	Tail 1: 300 mm, Tail 2: 1000 mm

*Caution: Operator must confirm voltage compatibility of prime mover and trailer.



8JA 227 440-091

Operating Voltage	Multivolt™*
Pins	7
Housing	Reinforced Composite
For Cable	11 mm to 18 mm
Contact Termination	Screw Contact

*Caution: Operator must confirm voltage compatibility of prime mover and trailer.

7P / Multivolt™ ABS/EBS Plug

Made of reinforced composite, with cover and rubber seals, and a high strength cable gland at the cable outlet.



8HG 227 440-001

Housing	Reinforced Composite
Suitable For	7P ABS/EBS Plugs 13P & 15P Plugs

Park Socket

Used when Plug is not connected to actual socket to prevent the exposure to environment.



8PD 004 508-031 - 7 Pin ISO7638-1 Socket Tester

Wiring Standards	ISO 7638-1 (24V)
------------------	------------------

ISO7638-1 ABS/EBS Socket Tester

Circuit testers make diagnosing wiring and lighting issues on trailers quick and easy in the field. The ABS/EBS Socket tester can be used on 24V and Multi-Volt ABS/EBS Sockets to confirm connectivity and functionality of the socket.

