

# WORK LIGHTS Overview



## LED WORK LIGHTS

Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number																								
	<ul style="list-style-type: none"> <li>Corrosion and impact resistant NanoSafe coating</li> <li>Specially developed thermal management with over-heating protection</li> <li>Light color similar to daylight</li> <li>Over-voltage protection</li> <li>Reverse polarity protection</li> <li>IP 6K9K (dust proof and withstands high pressure wash)</li> <li>IP 6K8 (immersion)</li> <li>Protected against EMC interference</li> <li>Approximate LED service life = 60,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 20-32 V</li> <li>Number of LEDs: 12</li> <li>Power Consumption: 84W</li> <li>Luminous Flux (measured): 7,600lm</li> <li>Light Temperature: 5000°K</li> <li>Ambient Temperature: -40°C to +90°C</li> <li>Housing Material: Aluminum + NanoSafe coating</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Nylon</li> <li>Connection: DT Connector</li> </ul>	<b>996197001</b> Zero Beam <b>996197041</b> Peril Beam <b>996197011</b> Close Range <b>996197021</b> Long Range Contains: • 1 LED Light • Instruction manual and installation components		<ul style="list-style-type: none"> <li>Corrosion and impact resistant NanoSafe coating</li> <li>Specially developed thermal management with over-heating protection</li> <li>Light color similar to daylight</li> <li>Over-voltage protection</li> <li>Reverse polarity protection</li> <li>IP 6K9K (dust proof and withstands high pressure wash)</li> <li>IP 6K8 (immersion)</li> <li>Protected against EMC interference</li> <li>Approximate LED service life = 60,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 9-32 V</li> <li>Number of LEDs: 4</li> <li>Power Consumption: 55W</li> <li>Luminous Flux (measured): 4,400lm</li> <li>Light Temperature: 5000°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Aluminum + NanoSafe coating</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Nylon</li> <li>Connection: DT Connector</li> </ul>	<b>995606541</b> Zero Beam <b>995606521</b> Peril Beam <b>995606501</b> Close Range <b>995606511</b> Long Range Contains: • 1 LED Light		<ul style="list-style-type: none"> <li>Thermo-conductive plastic housing for heavy duty</li> <li>Compact size</li> <li>Reverse polarity protection</li> <li>LED heat bypass</li> <li>Protection: IP 6K7 / IP 6K9K</li> <li>Approval: ECE R10 approved, RCM compliant</li> <li>Protected against EMC interference</li> </ul>	<ul style="list-style-type: none"> <li>Multi-voltage: 10.5-32 VDC</li> <li>Number of LEDs: 4</li> <li>Power Consumption: 26 W</li> <li>Luminous Flux (measured): 1,850 lm</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Nylon</li> <li>Light Temperature: 5000 K</li> <li>Connection: DT Connector</li> </ul>	<b>996488501</b> Close Range <b>996488511</b> Long Range Contains: • 1 LED Light • Instruction manual		<ul style="list-style-type: none"> <li>Developed specifically for Mining applications</li> <li>Compact size</li> <li>Reverse polarity protection</li> <li>LED heat bypass</li> <li>Protection: IP 6K7 / IP 6K9K</li> <li>Approval: ECE R10 approved, RCM compliant</li> <li>Protected against EMC interference</li> </ul>	<ul style="list-style-type: none"> <li>Multi-voltage: 9-32 VDC</li> <li>Number of LEDs: 4</li> <li>Power Consumption: 15 W</li> <li>Luminous Flux (measured): 1,200lm</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Thermo plastic housing</li> <li>Optics: Lens &amp; Reflector</li> <li>Light Temperature: 5000 K</li> <li>Connection: DT Connector</li> </ul>	<b>996284051</b> Close Range <b>996284061</b> Long Range <b>996284071</b> Ambient Contains: • 1 LED Light • Instruction manual		<ul style="list-style-type: none"> <li>Specially developed thermal management with over-heating protection</li> <li>Light color similar to daylight</li> <li>Electronic DIC/DC conversion</li> <li>Over-voltage protection</li> <li>Reverse polarity protection</li> <li>IP 6K8 (immersion)</li> <li>IP 6K9K (dust proof/withstands high pressure wash)</li> <li>Protected against EMC interference</li> <li>Approximate LED service life = 60,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 9-33VDC</li> <li>Number of LEDs: 8</li> <li>Power Consumption: 56 W</li> <li>Luminous Flux (measured): 2,000lm</li> <li>Light Temperature: 6500°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Aluminum</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Nylon</li> <li>Connection: DT Connector</li> </ul>	<b>995606001</b> Close Range <b>995606011</b> Long Range Contains: • 1 LED Light • Instruction manual and installation components		<ul style="list-style-type: none"> <li>Specially developed thermal management with over-heating protection</li> <li>Light color similar to daylight</li> <li>Over-voltage protection</li> <li>Reverse polarity protection</li> <li>IP 6K8 (immersion)</li> <li>IP 6K9K (dust proof/withstands high pressure wash)</li> <li>Protected against EMC interference</li> <li>Approximate LED service life = 60,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 9-33VDC</li> <li>Number of LEDs: 9</li> <li>Power Consumption (@ 13.5VDC): 28 W</li> <li>Luminous Flux (measured): 2,500lm</li> <li>Light Temperature: 6500°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Aluminum</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Nylon</li> <li>Connection: DT Connector</li> </ul>	<b>995506001</b> Close Range <b>995506031</b> Long Range Contains: • 1 LED Light • Instruction manual and installation components		<ul style="list-style-type: none"> <li>Heavy duty flame retardant UV resistant polymer housing</li> <li>Integrated 4th generation ballast with brass cable screw connection</li> <li>2.5 times the light intensity of a 55W Halogen bulb</li> <li>Upright surface-mounted version for heavy-duty use</li> <li>Extra heavy duty stainless steel bracket</li> <li>Integrated recessed grip</li> <li>Resilient vibration damping for extreme impact and vibration stresses</li> <li>IP 6K9K (dust proof/withstands high pressure wash)</li> <li>Protected against EMC interference</li> <li>Approximate capsule service life = 2,500 hours</li> <li>Meets HELLA Norm N67001 - Class 9</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12VDC</li> <li>Light Source: D1S 35W Capsule</li> <li>Ballast Unit: Gen 4</li> <li>Power Consumption: 42W</li> <li>Luminous Flux (measured): 2,000lm</li> <li>Light Temperature: Approx. 4200°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Aluminum</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Cable w/ DT Connector</li> </ul>	<b>996242111</b> Close range <b>996134567</b> Long range <b>996234021</b> Close range - Retail Contains: • 1 LED Light • Instruction manual and installation components		<ul style="list-style-type: none"> <li>Heavy duty flame retardant UV resistant polymer housing</li> <li>Integrated 4th generation ballast with brass cable screw connection</li> <li>2.5 times the light intensity of a 55W Halogen bulb</li> <li>Upright surface-mounted version for heavy-duty use</li> <li>Extra heavy duty stainless steel bracket</li> <li>Integrated recessed grip</li> <li>Resilient vibration damping for extreme impact and vibration stresses</li> <li>IP 6K9K (dust proof/withstands high pressure wash)</li> <li>Protected against EMC interference</li> <li>Approximate capsule service life = 2,500 hours</li> <li>Meets HELLA Norm N67001 - Class 9</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12VDC</li> <li>Light Source: D1S 35W Capsule</li> <li>Ballast Unit: Gen 4</li> <li>Power Consumption: 42W</li> <li>Luminous Flux (measured): 2,000lm</li> <li>Light Temperature: Approx. 4200°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: Aluminum</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Cable w/ DT Connector</li> </ul>	<b>996242501</b> Close Range <b>996242541</b> Long Range Contains: • 1 LED Light • Instruction manual and installation components		<ul style="list-style-type: none"> <li>Upright surface-mounted version for heavy-duty use</li> <li>Fiber-glass reinforced plastic housing</li> <li>Integrated recessed grip</li> <li>Extra heavy duty stainless steel bracket</li> <li>IP 6K9K (dust proof and withstands high pressure wash)</li> <li>EMC Class 4 per CISPR 25</li> <li>Approximate capsule service life = 2,500 hours</li> <li>Meets HELLA Norm N67001 - Class 4</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 VDC</li> <li>Light Source: H8/9/005</li> <li>Power Consumption: 42W</li> <li>Luminous Flux (measured): 2,600 lm</li> <li>Light Temperature: Approx. 4200°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Integrated DT</li> <li>Mounting: Pedestal, Pendant</li> <li>Bracket: SS Long Stud</li> </ul>	<b>996261721</b> Close Range - 12 V <b>996261771</b> Close Range - 12 V Red/Blue Contains: • 1 LED Light • Instruction manual and installation components

## XENON WORK LIGHTS

Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number
	<ul style="list-style-type: none"> <li>Fiber-glass reinforced plastic housing</li> <li>Heavy Duty Bracket</li> <li>IP6K9K (dust proof and withstands high pressure wash)</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N67001 - Class 3</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 VDC</li> <li>Illumination: Close and Long Range</li> <li>Light Source: 12V H3</li> <li>Power Consumption: 55W</li> <li>Luminous Flux (measured): 1,150 cdm</li> <li>Light Temperature: Approx. 2500 K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: 4-point (gal-Zn)</li> </ul>	<b>996134901</b> Long range - Box <b>996134567</b> Long range - 30 Pieces <b>996234021</b> Close range - Retail Contains: • 1 LED Light		<ul style="list-style-type: none"> <li>Fiber-glass reinforced plastic housing</li> <li>Heavy Duty Bracket</li> <li>IP6K9K (dust proof and withstands high pressure wash)</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N67001 - Class 3</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 VDC</li> <li>Illumination: Close and Long Range</li> <li>Light Source: 2x 12V H3</li> <li>Power Consumption: 110W</li> <li>Luminous Flux (measured): 1,050 cdm</li> <li>Light Temperature: Approx. 2500 K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: Stud (gal-Zn)</li> </ul>	<b>997506301</b> Close range <b>358115111</b> Close range <b>358115291</b> Close range <b>358115131</b> 24 V - Close range Contains: • 1 LED Light		<ul style="list-style-type: none"> <li>Heavy duty flame retardant UV resistant polymer housing</li> <li>Upright surface-mounted version for heavy-duty use</li> <li>IP 6K9K (dust proof and withstands high pressure wash)</li> <li>Fiber-glass reinforced plastic housing</li> <li>Free Form Reflector optimizes light distribution</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N2010-02</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12VDC</li> <li>Light Source: H8/9/005</li> <li>Power Consumption: 65W</li> <li>Luminous Flux (measured): 1,800 cdm</li> <li>Luminous Efficacy (lumens per watt): 61lm/W</li> <li>Light Temperature: Approx. 2500°K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: Stud (gal-Zn)</li> </ul>	<b>996186051</b> Close range Contains: • 1 LED Light

## HALOGEN WORK LIGHTS

Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number	Product Image	Features	Specifications	Part Number
	<ul style="list-style-type: none"> <li>Fiber-glass reinforced compact plastic housing</li> <li>Heavy Duty Bracket</li> <li>IP6K9K (dust proof and withstands high pressure wash)</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N67001 - Class 7.1</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 VDC</li> <li>Illumination: Close Range</li> <li>Light Source: 2V H3</li> <li>Power Consumption: 55W</li> <li>Luminous Flux (measured): 1,100 cdm</li> <li>Light Temperature: Approx. 2500 K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: M10 Stud (gal-Zn)</li> </ul>	<b>996176491</b> Close range - Box Contains: • 1 LED Light		<ul style="list-style-type: none"> <li>Fiber-glass reinforced plastic housing</li> <li>Heavy Duty Bracket</li> <li>IP6K9K (dust proof and withstands high pressure wash)</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N67001 - Class 3</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 or 24 VDC</li> <li>Illumination: Close Range</li> <li>Light Source: 2x 12V H3</li> <li>Power Consumption: 55W</li> <li>Luminous Flux (measured): 1,050 cdm</li> <li>Light Temperature: Approx. 2500 K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: 4-point (gal-Zn)</li> </ul>	<b>358115281</b> 12V - Close range <b>358470911</b> 24V - Close range Contains: • 1 LED Light		<ul style="list-style-type: none"> <li>Free Form Reflector optimizes light distribution</li> <li>Fiber-glass reinforced plastic housing</li> <li>Heavy Duty Bracket</li> <li>IP 6K9K (dust proof and withstands high pressure wash)</li> <li>Approximate bulb service life = 450 hours</li> <li>Meets HELLA Norm N67001 - Class 3</li> </ul>	<ul style="list-style-type: none"> <li>Voltage: 12 VDC</li> <li>Illumination: Close and Long Range</li> <li>Light Source: 2x 12V H3</li> <li>Power Consumption: 110W</li> <li>Luminous Flux (measured): 1,050 cdm</li> <li>Light Temperature: Approx. 2500 K</li> <li>Ambient Temperature: -40°C to +50°C</li> <li>Housing Material: HD Plastic</li> <li>Optics: Lens &amp; Reflector</li> <li>Lens Material: Glass</li> <li>Connection: Wire leads</li> <li>Mounting: Pedestal</li> <li>Bracket: Stud (gal-Zn)</li> </ul>	<b>358115041</b> Close range <b>358115071</b> Close range <b>358115061</b> Long range Contains: • 1 LED Light

For more information on HELLA work lights, visit our website:



www.hellahd.com