



Opel Astra H: replace thermostat

Data sheet	
Manufacturer	Opel
Vehicle model	Astra H
Engine	1.7 CDTi
Engine code	Z17DTR / A17DTR
Model year	2007 - 2010
Please note	The coolant thermostat has been concealed below the intake manifold.

Important safety note

Opel Astra H: replacing the thermostat including instructions and note

In the Opel Astra H, the coolant thermostat has been concealed below the intake manifold.

Proceed as follows to remove it:

- Disconnect the battery (potentially write down the radio code before you disconnect the battery)
- Remove the battery and battery bracket ([Fig. 1](#))
- Remove the hose and lid from the thermostat housing

You can now see the thermostat ([Fig. 2](#)) and replace it.

Tip

The coolant temperature sensor has been installed to the left of the thermostat. Pay particular attention to the short coolant hose behind it. In some cases, it has been damaged, thus causing a leak that is hard to find.



Figure 1: Removing the battery and battery bracket



Figure 2: Thermostat visible and ready to be replaced

Reprinting, distribution, reproduction, exploitation in any form or disclosure of the contents of this document, even in part, is prohibited without our express, written approval and indication of the source. The schematic illustrations, pictures and descriptions serve only for the purposes of explanation and representation of the instructions and cannot be used as a basis for installation or assembly work. All rights reserved.