

Mercedes Benz Vejledning om bremsereparation | HELLA

Mercedes Benz Vejledning om reparation af bremser Alle modeller med SBC-bremsesystem Systeminformation Modelserierne R230 og W211 var de første serieproducerede modeller, der var udstyret med det elektrohydrauliske bremsesystem Sensotronic Brake Control (SBC). Systemet foretager under visse forudsætninger en sikkerhedstest (Pre-Drive-Check), hvorved der kortvarigt opbygges bremsetryk. Derfor skal systemet altid deaktiveres inden reparation. Hvis det ikke deaktiveres, kan teknikeren komme til skade, hvis systemet evt. opbygger tryk. Deaktivering af bremsesystemet Der kræves et passende diagnoseapparat til deaktivering af SBC-systemet. Ved deaktivering aflastes systemtrykket, og højtrykspumpen slås fra. Desuden vises der et rødt advarselssymbol i instrumentgruppen. I denne tilstand er bremsesystemet ikke funktionsdygtigt. Systemet skal aktiveres igen efter reparationen. Sikkerhedsanvisning Reparationer på SBC-bremsesystemet må kun foretages af uddannede fagfolk. Ved alle reparationer skal sikkerhedsforskrifter og monteringsvejledninger fra den pågældende system- eller bilproducent overholdes.

Information on brake repairs

All models with SBC brake systems

System information

With the market launch of the R230 and W211 series, series vehicles have now been fitted with the Sensotronic Brake Control (SBC) electro-hydraulic brake system for the first time. Under certain circumstances, the system runs a safety test (pre-drive check), during which the brake pressure is increased for a brief period. For this reason, the system must be deactivated before all repair operations. Failure to do so can lead to injury to the technician due to the automatic build-up of pressure.



Deactivating the brake system

A suitable diagnostic unit is required in order to deactivate the SBC system. When the system is deactivated, the system pressure is relieved and the high-pressure pump is switched off. At the same time, a red warning symbol appears on the instrument cluster.

The brake system cannot be operated when in this state. Once repair work is complete, the system must be reactivated.

Baugruppe:



SBC-Anlage deaktivieren

SBC-Anlage deaktivieren

SBC-Anlage aktivieren

SBC nach Bremsscheibenwechsel aktivieren

SBC nach Bremsbacken-/belagwechsel aktivieren

SBC-Bremssflüssigkeit wechseln/Bremse entlüften

Safety notice

- Repair work on SBC brake systems may only be carried out by trained specialists.
- For all repair work, please observe the safety and assembly instructions provided by the system or vehicle manufacturer in question.

Important safety note

Technical information and practical tips have been compiled by HELLA in order to provide professional support to vehicle workshops in their day-to-day work. The information provided on this website is intended for use by suitably qualified personnel only.

Reprinting, distribution, reproduction, exploitation in any form or disclosure of the contents of this document, even in part, is prohibited without our express, written approval and indication of the source. The schematic illustrations, pictures and descriptions serve only for the purposes of explanation and representation of the instructions and cannot be used as a basis for installation or assembly work. All rights reserved.