


BEACON KL ROTAFLEX / ROTAFIX

The products on this page have the following features:


Standard solution for robust applications

- Tough rotary beacons
- Optimum light power, focusing and distribution through the rotating unit made up of a high-sheen metallised parabolic reflector and bulb
- Compact design shape and unmistakable look
- Drive from motor with plastic worm gear
- Sturdy domes with smooth, easy-to-clean surface
- Approved according to ECE-R65
- LED successor is the RotaLED




BEACON KL ROTAFIX F*

12 V, amber	2RL 007 337-001
24 V, amber	2RL 007 337-011
12 V / 24 V, amber (twin-belt drive)	2RL 007 337-041
12 V, blue	2RL 007 337-101
24 V, blue	2RL 007 337-111




BEACON KL ROTAFLEX FL*

12 V, amber	2RL 006 846-001
24 V, amber	2RL 006 846-011
12 V, blue	2RL 006 846-101
24 V, blue	2RL 006 846-111



BEACON KL ROTAFIX M*

12 V, amber	2RL 007 337-021
24 V, amber	2RL 007 337-031
12 V, blue	2RL 007 337-121
24 V, blue	2RL 007 337-131



Luminous intensity in candela (cd)

TECHNICAL SPECIFICATIONS

	12 V	24 V
Nominal voltage (U _N)		
Operating voltage (U _B)	10.8 – 13.8 V	21.6 – 27.6 V
Interference suppression	Power-controlled class 3 (CISPR 25)	
Engine speed	160 rpm	
Power consumption of bulb	55 W	70 W
Total current consumption	5.5 A	3.5 A
Operating temperature range	-40°C to +60°C	
Installation	From above and below	
Position of use	Upright	
Protection category	IP 5K4K, IP X9K (resistant to dust and high-pressure jet cleaners)	

TYPE APPROVAL

Lighting technology homology, amber	006509, (ECE-R65)
Lighting technology homology, blue	006513, (ECE-R65)
EMC compatibility	032181

* Other colors available on request.