




KL JuniorPlus



KL JuniorPlus F



KL JuniorPlus FL



KL JuniorPlus M

Product advantages

- Beacon range with a modern design and an attractive price/performance ratio
- Maintenance-free belt drive on bearings, for constant rotation frequency and optimum running smoothness
- Multi-voltage function: by moving the drive belt and replacing the bulb, 12 or 24 V operation is possible
- Sturdy, easy-to-clean dome with handy pressure-point closure system

Technical data

	12 V	24 V
Rated voltage (U_N):	12 V	24 V
Operating voltage (U_B):	10.8 – 13.8 V	21.6 – 27.6 V
Interference suppression:	Conducted class 3 (CISPR25)	
Rotational speed:	180 rpm	
Total current consumption:	5 A	3 A
Operating temperature range:	-40 °C to +60 °C	
Mounting (KL JuniorPlus F):	From below	
Protective category:	IP 5K4K, IP 9K (resistant to high-pressure cleaner)	

Type approval:

Lighting homologation:	Ⓔ 002140
EMC compatibility:	Ⓔ 022954
General:	ECE-R65

Product variants	Part number
KL JuniorPlus F , fixed attachment, blue, 12 V	2RL 008 965-031
KL JuniorPlus F , fixed attachment, blue, 24 V	2RL 008 965-041
KL JuniorPlus FL , flexible pipe-socket fixing, blue, 12 V	2RL 008 967-031
KL JuniorPlus FL , flexible pipe-socket fixing, blue, 24 V	2RL 008 967-041
KL JuniorPlus M , magnetic fixing, blue, 12 V	2RL 008 966-031

Further accessories and spare parts can be found in the overall brochure "Emergency Vehicles".

